

# Ausführungen | Versions ST-264

Bezeichnung Description	E	A	SW	L	Durchfluss Flow rate	Material Material	Gewicht Weight	Druck Pressure	Artikel-Nr. Item-No.
	Eingang Inlet	Ausgang Outlet							
Hochdruck- Rückschlagventil High pressure check valve	G1/4 IG G1/4 female	G1/4 IG G1/4 female	19 mm	62 mm	25 l/min 6,6 US gal/min	Edelstahl Stainless steel	0,104 kg	400 bar 5800 psi	20 0264 500
Hochdruck- Rückschlagventil High pressure check valve	G1/4 IG G1/4 female	G1/4 IG G1/4 female	19 mm	62 mm	25 l/min 6,6 US gal/min	Messing Brass	0,110 kg	150 bar 2170 psi	20 0264 510
Hochdruck- Rückschlagventil High pressure check valve	G3/8 IG G3/8 female	G3/8 IG G3/8 female	22 mm	65 mm	40 l/min 10,4 US gal/min	Edelstahl Stainless steel	0,136 kg	400 bar 5800 psi	20 0264 520
Hochdruck- Rückschlagventil High pressure check valve	G3/8 IG G3/8 female	G3/8 IG G3/8 female	22 mm	65 mm	40 l/min 10,4 US gal/min	Messing Brass	0,145 kg	150 bar 2170 psi	20 0264 530
Hochdruck- Rückschlagventil High pressure check valve	G1/2 IG G1/2 female	G1/2 IG G1/2 female	27 mm	90 mm	80 l/min 21 US gal/min	Edelstahl Stainless steel	0,314 kg	400 bar 5800 psi	20 0264 540

## Technische Daten | Specification

Material		Material	Edelstahl		Stainless steel
			Messing		Brass
Temperatur		Temperature	90 °C		190 °F
Öffnungsdruck		Opening pressure	0,14 bar 2 psi		0,14 bar 2 psi

