



SUTTNER

A M E R I C A C O M P A N Y

PRESSURE WASHER COMPONENTS & ACCESSORIES



Higher PSI
Catalog
2023-2024

Table of Contents

ABOUT US.....Page 3

SPRAY GUNS.....Page 4

LANCES.....Page 5 & 6

NOZZLES.....Page 7

SCREW NIPPLES.....Page 8

PLUGS & SOCKETS.....Page 9

SCREW COUPLINGS.....Page 10

FLOW SWITCH & FOOT ACTUATED VALVE.....Page 11

For Nearly

60 Years: The SUTTNER brand is recognized for many of the modern innovations in the high pressure cleaning applications today.

- 375 employees world wide.
- 430,000 square foot factory space worldwide.
- Suttner supplies components to more than 75 countries.
- In-house production of 95% of **ALL** products sold.

Training: We are committed to training, we believe the more knowledge the customer has, the easier the selling process.

Innovation: Suttner strives to develop 2 products each month on average.

Reliability: We strive to fill orders in a timely manner.

Integrity: Is a concept of consistency of actions, values, methods, measures, principles, expectations and outcomes.

Consistency: Our integrity guides us to supply our customers with the parts and accessories in a manner that they request.

Quality: Product branded with the SUTTNER name is designed and manufactured with quality products that features comfortable and easy function use that customers have come to expect for nearly **60 years**.

Discipline: Our management team has the business acumen to stay true to business strategies that partner with like-minded customers.

Loyalty: A shared business loyalty model combining quality of product and service leads to mutually satisfying and profitable relationships.

Partnership: Development of successful, long term, strategic relationships based on achieving best practice and sustainable competitive advantages.

Knowledge: Our North American staff average 18 years of industry experience.

Location: Central USA warehouse for quick shipping direct to all locations.

Our management team is driven by a true commitment to customer's needs. The Suttner team has extensive experience and provides the technical support needed. We specialize in personal service, spending time with customers over the phone or in person to diligently understand customer's needs and markets.



ST-2750 SPRAY GUN (*tungsten carbide ball valve*)

New patented valve kit and tungsten carbide ball with special valve seat. Economical 7300 PSI spray gun with relax action trigger.

ORDER #	PRESSURE	TEMP.	FLOW RATE	INLET	OUTLET	WEIGHT	BOX QTY
202750510	7300 PSI	300° F	8 GPM	3/8" FPT	1/4" FPT	1.32 lb	50

Repair Kit: #202750495

- Relax-Action™ is designed for operators and applications with longer periods of cleaning time
- The Relax-Action™, German Engineered Technology reduces trigger pulling force by 40% and holding force up to 90% compared to standard spray guns
- Stainless steel housing and valve components
- Private Label Availability



ST-3600 SPRAY GUN (*high pressure, high volume*)

Our highest pressure rated industrial spray gun

ORDER #	PRESSURE	TEMP.	FLOW RATE	INLET	OUTLET	WEIGHT	BOX QTY
203600600	8700 PSI	300° F	21 GPM	1/2" FPT	1/2" FPT	2.58 lb	10
203600610	8700 PSI	300° F	21 GPM	3/8" FPT	1/4" FPT	2.58 lb	10

Repair Kit: #203600490
Without Valve Cone: #203600491

- Forged stainless steel housing, piston and malleable seat
- Special heat and chemical resistant seals
- Private Label Availability

Legend:



Private Label Availability: Promote your company name or logo with customizing select spray guns' label.



Relax Action: German Engineered Technology reduces trigger pulling force by 40% and holding force up to 90% compared to standard spray guns. It is designed for operators and applications with longer periods of cleaning time.

ST-001 LANCES *(stainless steel)*

ORDER #	PRESSURE	TEMP.	LENGTH	INLET	OUTLET	WEIGHT	BOX QTY
070009004	7300 PSI	300° F	36 in.	1/4" MPT	1/4" MPT	.80 lb	50

- Threads are rolled on providing consistent sealing and four times the strength than cut threads
- **Chemical resistant**



ST-002 MOLDED GRIP LANCES *(stainless steel)*

ORDER #	PRESSURE	TEMP.	LENGTH	INLET	OUTLET	WEIGHT	BOX QTY
070012002	7300 PSI	300° F	47 in.	1/4" MPT	1/4" MPT	1.88 lb	20

- Comfort technology designed molded grip conforms to the curvature of the hand, allowing to comfortably change positions
- Linear aeration provides continuous air flow between hand and exclusive Suttner "star shaped" grip
- Grip is directly molded on the lance providing protection and strength
- Favorite molded grip lance design in the industry
- Threads are rolled on providing consistent sealing and four times the strength than cut threads
- **Chemical resistant**





ST-3600 LANCES *(stainless steel)*

This **8700 PSI** rated stainless steel lance is the perfect fit for the ST-3600 spray gun. The stainless steel construction is ideal for chemical applications.

ORDER #	PRESSURE	TEMP.	LENGTH	INLET	OUTLET	WEIGHT
203600400	8700 PSI	300° F	19 in	1/2" MPT	1/4" FPT	2.35 lb
203600402	8700 PSI	300° F	39 in	1/2" MPT	1/4" FPT	3.00 lb
203600450	8700 PSI	300° F	19 in	1/2" MNPT	1/4" FNPT	2.35 lb
203600452	8700 PSI	300° F	39 in	1/2" MNPT	1/4" FNPT	3.00 lb

- Threads are rolled on providing consistent sealing and four times the strength than cut threads
- Adjustable handle
- **Chemical resistant**

ST-154 DUAL LANCES *(high psi, stainless steel)*

The side handle grip makes an effortless adjustment of the water jet during operation possible. A long casting point jet or a progressive cone like spray jet can be set.

ORDER #	LENGTH	PRESSURE OUTLET	NOZZLE	WEIGHT
200154500	38 in	1/4" F x 1/4" Soap	65° x 30.0	2.62 lb
200154550	50 in	1/4" F x 1/4" Soap	65° x 30.0	3.46 lb

PRESSURE	TEMP.	INLET
7250 PSI	300° F	1/4" MPT

Repair Kits: Handle Assembly #200154400
Complete Valve Kit #200154490



- High or low pressure operation is controlled by twisting the side handle
- Side handle helps manage the lance with ease for longer working periods
- Lance is equipped with a 65° x 30.0 brass soap nozzle
- Threads are rolled on providing consistent sealing and four times the strength than cut threads

ST-559 TURBO NOZZLES (*tungsten carbide nozzle & seat*)


The increased tearing action of the rotating spray is ideal for hard surface applications, such as concrete graffiti cleaning or caked on mud on heavy equipment

ORDER #	PRESSURE	TEMP.	ORIFICE	INLET	WEIGHT	REPAIR KIT
200559620	8700 PSI	190° F	2.0	1/4" FPT	1.32 lb	200559120
200559630	8700 PSI	190° F	3.0	1/4" FPT	1.32 lb	200559130
200559640	8700 PSI	190° F	4.0	1/4" FPT	1.32 lb	200559140
200559650	8700 PSI	190° F	5.0	1/4" FPT	1.32 lb	200559150
200559655	8700 PSI	190° F	5.5	1/4" FPT	1.32 lb	200559155
200559660	8700 PSI	190° F	6.0	1/4" FPT	1.32 lb	200559160

- Increases cleaning efficiency as much as 200%
- The 0° rotation creates a cleaning and tearing action
- Ideal for hard surfaces
- Improved materials for a longer life
- Tungsten carbide nozzle and sealing seat
- Orifice size stamped on inlet nut



ALWAYS START TURBO NOZZLE IN A DOWNWARD POSITION.
THE USE OF A TURBO STRAINER IS RECOMMENDED FOR ALL TURBO NOZZLES.



ALSO AVAILABLE:

1/2" Inlet (minimum quantities)

ST-49 ROTATING SEWER NOZZLES

ORDER #	PRESSURE	O.D.	FLOW RATE	NOZZLE SIZE	REAR JETS	SIDE JETS	INLET
200049950	7252 PSI	.47"	6.6 GPM	050	2	2	1/8" FBSP
200049970	7252 PSI	.47"	9.2 GPM	070	2	2	1/8" FBSP
200049951	7252 PSI	.47"	6.6 GPM	050	2	2	1/8" FPT
200049971	7252 PSI	.47"	9.2 GPM	070	2	2	1/8" FPT

- Hardened stainless steel
- Excellent interior cleaning nozzle
- Slower rotor speed for higher cleaning performance
- Ideal for cleaning heat exchange tubes



#200049950

Screw Nipples



ST-41 SCREW NIPPLES (stainless steel)

7250 PSI screw nipples, ideal for connections that have to be changed. Multiple versions to meet all of the connections applications.

	ORDER #	PRESSURE	YOKE/I.D.	INLET	OUTLET	WEIGHT
A	040002300	7250 PSI	M14	1/4" FPT	M22	.12 lb
B	040002210	7250 PSI	M14	1/4" MPT	M22	.14 lb
C	040002200	7250 PSI	M14	3/8" FPT	M22	.10 lb
D	040002190	7250 PSI	M14	3/8" MPT	M22	.10 lb

TEMP.	BAG QTY
300° F	10

- Allow connection of male and female 1/4" and 3/8" pipe thread applications
- Stainless steel construction for chemical and food applications

Comparable rated components must be used together

10,150 PSI



ST-741 SCREW NIPPLES (stainless steel)

Ideal for connections that have to be changed. Multiple versions to meet all of the connections applications.

ORDER #	PRESSURE	TEMP.	YORK/I.D.	SIZE	WEIGHT
200741501	10,150 PSI	300° F	M15	3/8" MBSP x M24	.16 lb
200741502	10,150 PSI	300° F	M15	3/8" FBSP x M24	.16 lb
200741503	10,150 PSI	300° F	M15	1/2" MBSP x M24	.16 lb
200741504	10,150 PSI	300° F	M15	1/4" FBSP x M24	.16 lb

O-ring: #050001000

- Allows connection of male and female M24 fittings and 1/4", 3/8" and 1/2" pipe thread applications
- Stainless steel construction for chemical and food applications
- O-ring: EPDM



Q.C. PLUGS (303 stainless steel)

ORDER #	EATON #	PRESSURE	DESCRIPTION	BOX QTY	WEIGHT
1000SS140	LL2-T15	7500 PSI	1/4" MPT Plug	25	.06 lb
1000SS150	LL2-T16	7500 PSI	1/4" FPT Plug	25	.06 lb

Comparable rated components must be used together

ECONOMY Q.C. STAINLESS STEEL PLUGS

ORDER #	PRESSURE	DESCRIPTION	BAG QTY	WEIGHT
1000SS141	7500 PSI	1/4" M Plug	25	.06 lb
1000SS151	7500 PSI	1/4" F Plug	25	.06 lb



Comparable rated components must be used together

ECONOMY Q.C. STAINLESS STEEL SOCKETS

ORDER #	PRESSURE	DESCRIPTION	O-RING	BAG QTY	WEIGHT
20SS45701	7500 PSI	1/4" M Socket	Buna	10	.22 lb
20SS45711	7500 PSI	1/4" F Socket	Buna	10	.16 lb



Comparable rated components must be used together

Q.C. STAINLESS STEEL SOCKETS (303 stainless steel)

Couplers are used anywhere high pressure connections are frequently connected and disconnected. Ideal for quick change of quick nozzles and spray guns.



ORDER #	EATON #	PRESSURE	DESCRIPTION	O-RING	BOX QTY	WEIGHT
20SS45700	LL2-S15	7500 PSI	1/4" MPT Socket	Buna	200	.22 lb
20SS45710	LL2-S16	7500 PSI	1/4" FPT Socket	Buna	200	.16 lb

- Knurling on socket sleeve helps to grip ball lock
- Eaton quick couplers are the original, invented in 1915 and are still the number one name for quality couplers
- Interchanges easily with Suttner products and other major brands

Comparable rated components must be used together

Screw Couplings



ST-740 SCREW COUPLINGS (stainless steel)

Ideal for connections that have to be changed. Multiple versions to meet all of the connections applications.

ORDER #	PRESSURE	TEMP.	YOKE/I.D.	SIZE	WEIGHT
200740501	10,150 PSI	300° F	M15	3/8" MBSP x M24	.35 lb
200740502	10,150 PSI	300° F	M15	3/8" FBSP x M24	.35 lb
200740503	10,150 PSI	300° F	M15	1/2" MBSP x M24	.35 lb
200740504	10,150 PSI	300° F	M15	1/4" MBSP x M24	.35 lb

O-ring: #050000408
Support ring: #050000407

- Allows connection of male and female M24 fittings and 1/4", 3/8" and 1/2" pipe thread applications
- Stainless steel construction for chemical and food applications
- O-ring: HNBR



ST-40 SCREW COUPLINGS (stainless steel)

7250 PSI screw couplings, ideal for connections that have to be changed. Multiple versions to meet all of the connections applications.

	ORDER #	PRESSURE	TEMP.	YORK /I.D.	INLET	OUTLET	WEIGHT
A	200040900	7250 PSI	300° F	M14	1/4" FPT	M22	.24 lb
B	200040910	7250 PSI	300° F	M14	1/4" MPT	M22	.22 lb
C	200040930	7250 PSI	300° F	M14	3/8" MPT	M22	.22 lb
D	200040940	7250 PSI	300° F	M14	3/8" FPT	M22	.20 lb

O-ring: #050000120

- Allow connection of male and female M22 fitting and 1/4" and 3/8" pipe thread applications
 - Stainless steel construction for chemical and food applications
- Comparable rated components must be used together**

Flow Switch and Foot Actuated Valve

ST-505 FLOW SWITCH (stainless steel, 8700 psi)

Vertical mounting position and free floating brass magnet configuration

ORDER #	PRESSURE	TEMP.	FLOW RATE
200505706	75 - 8700 PSI	180° F	1.0 - 7.8 GPM

INLET	OUTLET	WEIGHT	BOX QTY
3/8" FPT	3/8" FPT	.90 lb	50

Replacement reed switch: #200005435

Replacement float: #200005300



- Mounts further downstream in pumping system than traditional vacuum switches, thereby minimizing potential leak points that can cause vacuum switches to close
- Easy brass reed switch replacement
- **3/8" bonded seal #78888389 is recommended to seal inlet and outlet threads**

ST-550 FOOT ACTUATED VALVE (7300 psi)


Foot controlled valves allow both hands to be free to control the sewer hose pulling hose back and forth to flush pipes

ORDER #	PRESSURE	TEMP.	INLET	OUTLET	FLOW RATE	WEIGHT
200550500	7300 PSI	300° F	1/4" FPT	1/4" FPT	10.5 GPM	9 lb

Repair Kit: #203600490



- Inlet and outlet are positioned to help keep hose out of the way
- Stainless steel construction
- Pedal and valve are in protective housing



SUTTNER

A M E R I C A C O M P A N Y

PRESSURE WASHER COMPONENTS & ACCESSORIES

With almost **60** years of experience, Suttner America Company is one of the worldwide leading manufacturers of high quality products for the cleaning industry

Address:

14864 West Ridge Ln.
Dubuque, IA 52003

Fax:

(563) 556.3038
(800) 821.0660

Phone:

(563) 556.3212
(800) 831.0660

Email:

sales@suttner.com

Web:

www.suttner.com

GERMAN ENGINEERED TECHNOLOGY